

Superstrip

Industrial and Institutional Floor Finish Stripper

Description:

Strip-It is a concentrated mixture of detergents and ethanalamines specially formulated to break the chemical film formed by floor finishes. It works especially well stripping acrylic floor waxes.

Directions For Use:

Strip-It should be added at a rate of 2 to 12 oz per gallon of warm water for use as a mopping, wiping or fabric cleaning solution. This dilution should be mopped, sponged or sprayed on the floor, and rinse mopped, sponged or wiped with clean cold water. For extremely soiled or heavy traffic areas, precleaning of area using MAG-IT's Speed-It high alkaline cleaner is recommend prior to floor finish stripping to maximize effectiveness. After stripping the finish a clean water rinse and allowing the floor to dry completely is recommended before application of the new floor finish.

Typical Properties:

BOILING POINT: 212°F

SPECIFIC GRAVITY: 1.05

PERCENT VOLATILE BY VOLUME: 87.75%

EVAPORATION RATE (H₂O = 1): 1

SOLUBILITY IN WATER: Complete

APPEARANCE AND ODOR: Clear yellow/green liquid with an ammonia odor.

pH AS RECEIVED: 10.5 (estimated)

Disclaimer:

The information and recommendations contained herein are to the best of MAG-IT's knowledge and belief, accurate and reliable as of the date issued. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his own use of the product described herein. Since the actual use of this product is beyond the control of MAG-IT, no guarantee, expressed or implied, is made by MAG-IT.