

MAG-IT
Product Bulletin

MAG-IT

E Z STRIP

Alkaline Paint Stripper Concentrate

Description:

MAG-IT E Z STRIP is a concentrated mixture of sodium hydroxide, alkaline builders, non-foaming detergents and sequestrants for use in stripping acrylic and enamel paints from metal and wood substrates.

Directions For Use:

MAG-IT E Z STRIP should be mixed in clean water at a rate of 1% to 5% by weight, or a minimum of about 4 ounces of dry product per gallon. This dilution can be used cold, but the process of dilution liberates heat. At elevated temperatures the product works faster than if used cold for the same amount of time. The degree of stripping is controlled by concentration, temperature and dwell time. Regardless of the operating temperature or cycle time, sufficient cycle time should be allowed for E Z STRIP to remove coatings to be stripped.

Typical Properties:

PERCENT VOLATILE BY VOLUME:	<2%
SOLUBILITY IN WATER:	Complete
APPEARANCE AND ODOR:	White free flowing powder.
pH, 1% SOLUTION IN WATER:	13

Disclaimer:

The information and recommendations contained herein are to the best of MAG-IT's knowledge and belief, accurate and reliable as of the date issued. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his own use of the product described herein. Since the actual use of this product is beyond the control of MAG-IT, no guarantee, expressed or implied, is made by MAG-IT.