

FLEETWASH

Vehicle Cleaner Concentrate

Description:

Fleetwash is a concentrated mixture of detergents and alkaline builders for use in cleaning heavily soiled surfaces of vehicles of all types. Fleetwash and was specifically formulated to be environmentally friendly.

Directions For Use:

Fleetwash should be used at a rate of 2 to 4 ounces per gallon of water for use in pressure washers as a feed solution. Fleetwash should be used at a rate of 1 to 2 ounces per gallon of water for use as a hand washing solution. For extremely soiled areas, the undiluted product can be applied with a spray bottle. The product should be allowed to sit for a minute or two, and then wiped or rinsed free, followed by a clean water rinse.

Rinsing is particularly important when applied to glass or acrylic canopy surfaces, as fouling of these surfaces may occur if the product is allowed to dry.

Typical Properties:

BOILING POINT: 212°F

SPECIFIC GRAVITY: 1.05

VAPOR PRESSURE: N/A

PERCENT VOLATILE BY VOLUME: 77.3%

VAPOR DENSITY (Air = 1): 1

EVAPORATION RATE (H₂O = 1): 0.9

SOLUBILITY IN WATER: Complete

APPEARANCE AND ODOR: Clear green viscous liquid with a lemon scent.

pH AS RECEIVED: \$12

Disclaimer:

The information and recommendations contained herein are to the best of MAG-IT, LLC's knowledge and belief, accurate and reliable as of the date issued. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his own use of the product described herein. Since the actual use of this product is beyond the control of MAG-IT, LLC, no guarantee, expressed or implied, is made by MAG-IT, LLC.